

FILTER OVERVIEW WITH SERVICE INTERVALS AND CAPACITIES

3E Series Compact Utility Tractors - 3025E (LL300001 -), 3032E (LL300001 -), 3038E (LL300001 -)

ENGINE

PRIMARY AIR FILTER
3025E – [M131802](#)

SECONDARY AIR FILTER
3025E – [M131803](#)

Check or replace after every 600 hours or as required.



ENGINE

DIESEL PARTICULATE FILTER (DPF)

3032E – [MIU803093](#)

3038E – [MIU803276](#)

See your John Deere™ dealer or qualified service provider.

FILTER PAK

3032E (S/N 610001 -), 3038E (S/N 610001 -) – [LVA21037](#)
M806419, LVA14703, LVA16054, M131802, MIU803127, MIU802421

Each kit contains above filters, offering a complete solution for your maintenance needs to keep your tractor running at peak performance.

ENGINE

PRIMARY FUEL FILTER
3025E, 3032E, 3038E – [MIU800645](#)

SECONDARY FUEL FILTER
3032E, 3038E – [MIU803127](#)

Replace after every 400 hours or annually, whichever occurs first.



ENGINE

OIL FILTER – [M806419](#)

Replace after every 400 hours or annually, whichever occurs first.

(Click here for [capacity](#))



ENGINE

WATER SEPARATOR
3025E – [M811032](#)

Replace after every 400 hours or annually, whichever occurs first.



TRANSMISSION/HYDRAULIC
OIL FILTER – [LVA16054](#)

Replace after every 400 hours or annually, whichever occurs first.

(Click here for [capacity](#))



HYDRAULIC

OIL FILTER – [LVA14703](#)

Replace after every 400 hours or annually, whichever occurs first.

(Click here for [capacity](#))



JOHN DEERE

Genuine Parts and Service

CAPACITIES

3E Series Compact Utility Tractors - 3025E (LL300001 -), 3032E (LL300001 -), 3038E (LL300001 -)

CAPACITIES (Approximate):

Fuel Tank:

..... 28.5 L (7.5 gal)

Cooling System:

Cool-Gard™ II

3025E, 3032E 4.9 L (1.3 gal)

3038E 5.2 L (1.37 gal)

Crankcase with Filter:

Plus-50™

..... 4.3 L (1.12 gal)

Transmission and Hydraulic System:

Hy-Gard™

..... 20.8 L (5.5 gal)

Front Axle:

Hy-Gard™

..... 3.8 L (1 gal)

[Return to Filter Overview](#)

