

REPLACEMENT PARTS GUIDE

3039R Compact Utility Tractor (MY24-) (PIN: 1LV3039R*PR100101-) (Worldwide Edition)

ENGINE

ENGINE OIL



[TY26668](#) (John Deere Plus-50™ II Premium)
(10W-30) (4.3 L (1.1 gal)) (WITH FILTER)
Change after every 400 hrs or annually.

SPIN-ON FUEL FILTER



[MIA882963](#) (FILTER KIT)
[MIU803127](#) (FILTER ELEMENT)
Change after every 400 hrs or annually.

AIR FILTER



[RE68048](#) (PRIMARY)
[RE68049](#) (SECONDARY)
Change after every 600 hrs or annually.

JD MULTI PURPOSE HD LITHIUM COMPLEX GREASE



[TY24416](#)
[TY26183](#)
Change As Required.

OIL FILTER



[M806419](#)
Change after every 400 hrs or annually,
whichever comes first.

FUEL-WATER SEPARATOR



[MIA885324](#) (FILTER KIT)
[MIU802421](#) (FILTER ELEMENT)
Change after every 400 hrs or annually.

FILTER PAK



[TA25768](#)

DIESEL PARTICULATE FILTER



[MIU803232](#)

AXLE

TIE ROD



[LVA19527](#) (MFWD)
[LVA10747](#) (SCV, BOOM LINKAGE, OOS)
[LVA10748](#) (SCV, BUCKET LINKAGE, OOS)

FRONT AXLE OIL



[TY22062](#) (John Deere Hy-Gard™)
(4.8 L (1.3 gal.))
Change every 600 hrs.

ELECTRICAL

KEY



[RE183935](#)

ROTARY SWITCH



[LVA21501](#) (14 V)

WET DISCHARGE BATTERY



[TY27831B](#) (12 V, 45 AH)

LED WORK LIGHT



[RE593795](#) (CAB) (12 V)

HEADLIGHT



[TA26778](#) (LED) (12 V)

V - BELT



[TR131486](#) (FOR ALTERNATOR) (75 A)
(LGTH = 1112 mm,
WIDTH = 13.4 mm,TK = 9.6 mm)
[LUV29375](#) (HVAC) (LGTH = 1508 mm,
WIDTH = 13.4 mm,TK = 9.6 mm)

FUEL TANK FILLER CAP



FILLER CAP
[AL213202](#)

CAB (IF EQUIPPED)



AIR FILTER

[MIU10010](#) (FRESH)
[MIU10011](#) (RECIRCULATION)

Service or Change every 50 hrs.

TRANSMISSION/ HYDRAULIC

TRANSMISSION/HYDRAULIC OIL



[TY22062](#) (John Deere Hy-Gard™)
HST - 26.4L (7.0 gal) PRT - 24.5 L (6.5 gal)
Change every 400 hrs.

OIL FILTER



[LVA23443](#) (FRONT PTO FILTER)
[LVA13065](#) (HYDRAULIC SUCTION FILTER
ELEMENT)



[LVA12726](#) (TRANSMISSION INLINE
HYDRAULIC OIL FILTER)

Change every 400 hrs.



JOHN DEERE
Genuine Parts and Service

CLICK PART NUMBER TO BUY

*See operator's manual for additional details.