



REPLACEMENT PARTS GUIDE

3046R Compact Utility Tractor (MY24-) (PIN: 1LV3046R*PR100101-) (Worldwide Edition)


ENGINE




ENGINE OIL
[TY26668](#) (John Deere Plus-50™ II Premium)
 (10W-30) (5.7 L (1.5 gal)) (WITH FILTER)
 Change after every 400 hrs or annually.




SPIN-ON FUEL FILTER
[MIA882963](#) (FILTER KIT)
[MIU803127](#) (FILTER ELEMENT)
 Change after every 400 hrs or annually.




AIR FILTER
[RE68048](#) (PRIMARY)
[RE68049](#) (SECONDARY)
 Change after every 600 hrs or annually.




JD MULTI PURPOSE HD LITHIUM COMPLEX GREASE
[TY24416](#)
GREASE GUN
[TY26183](#)
 Change As Required.




OIL FILTER
[M806419](#)
 Change after every 400 hrs or annually, whichever comes first.



FUEL-WATER SEPARATOR
[MIA885324](#) (FILTER KIT)
[MIU802421](#) (FILTER ELEMENT)
 Change after every 400 hrs or annually.




FILTER PAK
[TA25768](#)




DIESEL PARTICULATE FILTER
[MIU803232](#)

AXLE




TIE ROD
[LVA19527](#) (MFWD)
[LVA10747](#) (SCV, BOOM LINKAGE, OOS)
[LVA10748](#) (SCV, BUCKET LINKAGE, OOS)




FRONT AXLE OIL
[TY22062](#) (John Deere Hy-Gard™)
 (4.8 L (1.3 gal.))
 Change every 600 hrs.




ELECTRICAL




KEY
[RE183935](#)




ROTARY SWITCH
[LVA21501](#) (14 V)




WET DISCHARGE BATTERY
[TY27831B](#) (12 V, 45 AH)



LED WORK LIGHT
[RE593795](#) (CAB) (12 V)




HEADLIGHT
[TA26778](#) (LED) (12 V)




V - BELT
[TR131486](#) (FOR ALTERNATOR) (75 A)
 (LGTH = 1112 mm,
 WIDTH = 13.4 mm,TK = 9.6 mm)
[LUV29375](#) (HVAC) (LGTH = 1508 mm,
 WIDTH = 13.4 mm,TK = 9.6 mm)

FUEL TANK FILLER CAP




FILLER CAP
[AL213202](#)

CAB (IF EQUIPPED)




AIR FILTER
[MIU10010](#) (FRESH)
[MIU10011](#) (RECIRCULATION)
 Service or Change every 50 hrs.

TRANSMISSION/ HYDRAULIC



TRANSMISSION/HYDRAULIC OIL
[TY22062](#) (John Deere Hy-Gard™)
 HST - 26.4L (7.0 gal) PRT - 24.5 L (6.5 gal)
 Change every 400 hrs.



OIL FILTER
[LVA23443](#) (FRONT PTO FILTER)
[LVA13065](#) (HYDRAULIC SUCTION FILTER ELEMENT)
[LVA12726](#) (TRANSMISSION INLINE HYDRAULIC OIL FILTER)
 Change every 400 hrs.