




REPLACEMENT PARTS GUIDE


4052M Compact Utility Tractor (MY24-) (PIN: 1LV4052M*PR100101-) (Worldwide Edition)


ENGINE


- 


ENGINE OIL
[TY26669](#) (John Deere Plus-50™ II Premium)
 (10W-30) (5.4 L (5.7 qt))
 Change after every 400 hrs or annually.
- 


SPIN-ON FUEL FILTER
[MIA882963](#)
[MIU803127](#)
 Change after every 400 hrs or annually.
- 

AIR FILTER
[RE68048](#) (PRIMARY)
[RE68049](#) (SECONDARY)
 Change after every 600 hrs or annually.
- 


JD MULTI PURPOSE HD LITHIUM COMPLEX GREASE
[TY24416](#)
GREASE GUN
[TY26183](#)
 Change As Required.
- 

OIL FILTER
[M806419](#)
 Change after every 400 hrs or annually, whichever comes first.
- 

FUEL-WATER SEPARATOR
[MIA885324](#) (FILTER KIT)
[MIU802421](#) (FILTER ELEMENT)
 Change after every 400 hrs or annually.
- 

FILTER PAK
[TA25765](#)
- 


DIESEL PARTICULATE FILTER
[MIU803276](#)
- AXLE**


TIE ROD
[LVA14951](#) (ASSEMBLY)
[LVA14960](#) (LH)
[LVA14959](#) (RH)
- 


FRONT AXLE OIL
[TY22035](#) (John Deere Low Viscosity Hy-Gard™)
 (5.5 L (5.8 qt) - STANDARD)
 (8.0 L (8.5 qt) - HEAVY DUTY)
 Change every 600 hrs.





ELECTRICAL

- 


KEY
[RE183935](#)
- 

IGNITION SWITCH
[LVA21501](#)
- 


BATTERY
[TY26442B](#) (12 V)
- 


LED WORK LIGHT, OOS
[TA25218](#)
- 


HEADLIGHT
[TA26778](#) (LED) (12 V)
- FUEL & AIR**



FILLER CAP
[AL213202](#)
- TRANSMISSION/ HYDRAULIC**



TRANSMISSION/HYDRAULIC OIL
[TY22000](#) (John Deere Low Viscosity Hy-Gard™) (47.3 L (12.5 gal))
 Change after every 400 Hrs or annually.
- 

OIL FILTER
[RE45864](#) (TRANSMISSION)
[LVA10419](#) (HYDRAULIC)
[LVA23443](#) (FRONT PTO FILTER)
 Change after every 400 Hrs or annually.
- 

V - BELT
[TR131486](#) (ALTERNATOR) (LGTH = 1112 mm, WIDTH = 13.4 mm, TK = 9.6 mm)

