

REPLACEMENT PARTS GUIDE

4052R Compact Utility Tractor (MY24-) (PIN: 1LV4052R*PR100101-) (Worldwide Edition)

ENGINE




ENGINE OIL
[TY26669](#) (John Deere Plus-50™ II Premium)
 (10W-30) (5.4 L (5.7 qt))

Change every 400 hrs/ Annually.



SPIN-ON FUEL FILTER
[MIA882963](#)
[MIU803127](#)

Change after every 400 Hrs/Annually.



AIR FILTER
[RE68048](#) (PRIMARY)
[RE68049](#) (SECONDARY)

Change after every 600 Hrs or annually.



JD MULTI PURPOSE HD LITHIUM COMPLEX GREASE
[TY24416](#)
GREASE GUN
[TY26183](#)

Change As Required.



OIL FILTER
[M806419](#)

Change after every 400 Hrs or annually, whichever comes first.



FUEL-WATER SEPARATOR
[MIA885324](#) (SEPARATOR)
[MIU802421](#) (FILTER ELEMENT)

Change after every 400 Hrs or annually.



FILTER PAK
[TA25765](#)



DIESEL PARTICULATE FILTER
[MIU803276](#)

AXLE



TIE ROD
[LVA14951](#) (ASSEMBLY)
[LVA14960](#) (LH)
[LVA14959](#) (RH)



FRONT AXLE OIL
[TY22035](#) (John Deere Low Viscosity Hy-Gard™)
 (5.5 L (5.8 qt) - STANDARD)
 (8.0 L (8.5 qt) - HEAVY DUTY)

Change every 600 hrs.



ELECTRICAL



BATTERY
[TY26442B](#) (12 V)



HEADLIGHT
[TA26778](#) (LED) (12 V)



KEY
[RE183935](#)



IGNITION SWITCH
[LVA21501](#) (14 V)



LED WORK LIGHT
[TA25218](#) (OOS) (12 V)
[RE593795](#) (CAB) (12 V)

FUEL & AIR



FILLER CAP
[AL213202](#)

CAB



CAB FILTER
[MIU10010](#)

Clean or replace after every 50 hours.



RECIRCULATION AIR FILTER
[MIU10011](#)

Clean or replace after every 50 hours.

TRANSMISSION/ HYDRAULIC



TRANSMISSION/HYDRAULIC OIL
[TY22000](#) (John Deere Low Viscosity Hy-Gard™) (47.3 L (12.5 gal))
 Change after every 400 Hrs or annually



OIL FILTER
[RE45864](#) (TRANSMISSION)
[LVA10419](#) (HYDRAULIC)
[LVA23443](#) (FRONT PTO FILTER)

Change after every 400 Hrs or annually.



V - BELT
[TR131486](#) (ALTERNATOR) (LGTH = 1112 mm, WIDTH = 13.4 mm, TK = 9.6 mm)
[LUV29375](#) (HVAC) (LGTH = 1508 mm, WIDTH = 13.4 mm, TK = 9.6 mm)