

# REPLACEMENT PARTS GUIDE

4066M Compact Utility Tractor (MY20 - MY22)(PIN:1LV4066MKLL103638-1LV4066MEPN300734)(Worldwide Edition)



### ENGINE

**ENGINE OIL**  
[TY26669](#) (10W-30 PLUS-50™ II) (5.3 L (5.6 qt))  
 Change Every 200 Hrs or Annually, whichever comes first.

**FUEL FILTER**  
[MIU803127](#)  
 Change after every 400 Hrs/Annually.

**AIR FILTER**  
[RE68048](#) (PRIMARY)  
[RE68049](#) (SECONDARY)  
 Change every 400 hrs. or annually.

**JD MULTI PURPOSE HD LITHIUM COMPLEX GREASE**  
[TY6341](#)  
**GREASE GUN**  
[TY26183](#)  
 Change As Required.

**OIL FILTER**  
[M806419](#)  
 Change Every 200 Hrs or Annually, whichever comes first.

**FUEL/ WATER SEPARATOR**  
[MIU803221](#) (SEPARATOR)  
[MIU802421](#) (FILTER ELEMENT)  
 Change after every 400 Hrs. or annually.

**DIESEL PARTICULATE FILTER**  
[MIU802216](#)

**HOME MAINTENANCE KIT**  
[TA25765](#)

### ELECTRICAL

**LED WORK LIGHT, OOS**  
[AM143579](#) (12 V)

**KEY**  
[RE183935](#)

**ROTARY SWITCH**  
[LVA21501](#)

**BATTERY**  
[TY26442B](#) (12 V)

**HEADLIGHT**  
[R136239](#) (12 V 60/55 W)

### FUEL & AIR

**FILLER CAP**  
[AL213202](#)

### AXLE

**TIE ROD**  
[LVA14951](#) (ASSEMBLY)  
[LVA14960](#) (LH)  
[LVA14959](#) (RH)

**FRONT AXLE OIL**  
[TY22035](#) (John Deere Low Viscosity Hy-Gard™) (5.0 L (5.3 qt))  
 Change every 600 hrs.

### TRANSMISSION/ HYDRAULIC

**TRANSMISSION/HYDRAULIC OIL**  
[TY22000](#) (John Deere Low Viscosity Hy-Gard™) (47.3 L (12.5 gal))  
 Change after every 400 Hrs. or annually.

**V - BELT**  
[LVU29376](#) (LGTH = 1112 mm, WIDTH = 13.4 mm, TK = 9.6 mm)

**OIL FILTER**  
[RE45864](#) (TRANSMISSION)  
[LVA10419](#) (HYDRAULIC)  
 Change after every 400 Hrs. or annually.